



Voxter[®]
/ SCAN

Voxter[®] Scan Elite Edition

A unique backhand scanner
for mobile data capture

Mobile data capture by barcode scan has never been easier and more comfortable than with the new Voxter[®] Scan Elite Edition. The Voxter[®] Scan Elite only weighs 100 g making it very comfortable to wear.

Based on the latest imaging technology for decoding both 1D and 2D barcoding the Voxter[®] Scan Elite also features a globally unique auto-trigger scan function with distance sensor.

The Voxter[®] Scan Elite Edition is designed to withstand rugged industrial environments and is equipped with laser-supported targeting making the scanning process even easier.

Unique
auto-trigger
scan function
with distance
sensor

topsystem
/ VOICE SOLUTIONS



Voxter[®]
/ SCAN

THE backhand scanner for mobile data capture

The compact, rugged and extremely light-weight Voxter[®] Scan Elite Edition is worn comfortably on the back of the hand or in a belt cradle; a perfect integration into the existing workflow.

No additional action is required to trigger the scan function. The technologically exclusive auto-trigger function executes automatic barcode scanning at all times. Users have their hands free to perform vital tasks at any time. Even under the most demanding conditions, the Voxter[®] Scan Elite Edition is a reliable partner for fast and accurate data capture.

The Voxter[®] Scan Elite Edition is easily connected with other mobile or stationary devices via Bluetooth which makes it a possible enhancement for all voice directed mobile applications wherever additional data capture is required (e.g. capture of lot numbers, serial numbers or best before dates).

Product Profile

Size/Weight:

approx. 78 x 60 x 32 mm / approx. 100 g

Depth of scan field 10 mil Data Matrix:

5,3 cm – 20,3 cm

Scan pattern:

Imager

Barcode recognition:

automatic recognition of standard 1D and 2D barcodes

Scan function:

Distance sensor / auto-trigger

Bluetooth:

Ver 2.1 + EDR, range up to 30 m

Acoustic signals:

positive scan acknowledgement

Indicator (LED):

Charging, battery status, power, radio connection

Temperature:

Operating temperatures:

- 30° C up to + 50° C

Storage temperatures:

0° C up to + 55° C

Battery:

3.7 V lithium polymer exchangeable battery

Regular:

1,130 mAh, up to 8,000 scans

Extended:

2,260 mAh, up to 16,000 scans



LSP Solutions B.V.
Neonstraat 16
6718 WV Ede

Tel.: +31(0)88 - 2020300
Fax: +31(0)88 - 2020301
E-Mail info@LSPsolutions.com
Web: www.lspolutions.com